


LAGERBESTANDSLISTE

April 2012

Stand: 17.04.2012






Sorte DH, phosphatiert, EN 10270-1

84010-0020-220	DH, D:0,2, KSP20	54,00 kg
84010-0022-830	DH, D:0,22, KSP30	210,00 kg
84010-0025-830	DH, D:0,25, KSP30	634,10 kg
84010-0028-835	DH, D:0,28, KSP35	832,00 kg
84010-0030-835	DH, D:0,3, KSP35	805,00 kg
84010-0032-835	DH, D:0,32, KSP35	940,00 kg
84010-0034-230	DH, D:0,34, KSP30	54,60 kg
84010-0034-835	DH, D:0,34, KSP35	175,00 kg
84010-0035-835	DH, D:0,35, KSP35	525,00 kg
84010-0036-835	DH, D:0,36, KSP35	630,00 kg
84010-0038-835	DH, D:0,38, KSP35	70,00 kg
84010-0040-840	DH, D:0,4, KSP40	960,00 kg
84010-0045-840	DH, D:0,45, KSP40	160,00 kg
84010-0048-840	DH, D:0,48, KSP40	640,00 kg
84010-0050-840	DH, D:0,5, KSP40	760,00 kg
84010-0053-105	DH, D:0,53, R50	450,00 kg
84010-0055-835	DH, D:0,55, KSP35	665,00 kg
84010-0056-105	DH, D:0,56, R50	300,00 kg
84010-0056-835	DH, D:0,56, KSP35	210,00 kg
84010-0058-105	DH, D:0,58, R50	200,00 kg
84010-0060-105	DH, D:0,6, R50	950,00 kg
84010-0060-835	DH, D:0,60, KSP35	595,00 kg
84010-0063-835	DH, D:0,63, KSP35	350,00 kg
84010-0065-105	DH, D:0,65, R50	250,00 kg
84010-0070-105	DH, D:0,7, R50	200,00 kg
84010-0075-105	DH, D:0,75, R50	900,00 kg
84010-0080-105	DH, D:0,8, R50	550,00 kg
84010-0085-105	DH, D:0,85, R50	600,00 kg
84010-0085-425	DH, D:0,85, MSP250	255,00 kg
84010-0090-105	DH, D:0,9, R50	511,00 kg
84010-0095-105	DH, D:0,95, R50	311,00 kg
84010-0100-110	DH, D:1, R100	900,00 kg
84010-0110-110	DH, D:1,1, R100	99,00 kg
84010-0125-110	DH, D:1,25, R100	724,00 kg
84010-0130-110	DH, D:1,3, R100	106,00 kg
84010-0140-110	DH, D:1,4, R100	900,00 kg
84010-0150-110	DH, D:1,5, R100	731,50 kg
84010-0160-110	DH, D:1,6, R100	528,00 kg
84010-0170-110	DH, D:1,7, R100	803,50 kg
84010-0180-110	DH, D:1,8, R100	605,50 kg
84010-0180-425	DH, D:1,8, MSP250	255,50 kg
84010-0200-120	DH, D:2, R200	800,00 kg
84010-0210-120	DH, D:2,1, R200	866,00 kg
84010-0220-120	DH, D:2,2, R200	2547,00 kg
84010-0225-120	DH, D:2,25, R200	807,00 kg
84010-0230-120	DH, D:2,3, R200	621,00 kg
84010-0240-125	DH, D:2,4, R250	974,00 kg
84010-0260-125	DH, D:2,6, R250	1003,50 kg
84010-0300-130	DH, D:3, R300	908,00 kg
84010-0320-130	DH, D:3,2, R300	333,00 kg
84010-0350-130	DH, D:3,5, R300	871,50 kg
84010-0360-130	DH, D:3,6, R300	320,00 kg

84010-0400-130 DH, D:4, R300

916,00 kg

Sorte SH, phosphatiert, EN 10270-1



84020-0025-830	SH, D:0,25, KSP20	181,40 kg
84020-0030-835	SH, D:0,30, KSP35	209,90 kg
84020-0050-230	SH, D:0,5, KSP30	85,60 kg
84020-0050-840	SH, D:0,50, DIN355 35	363,20 kg
84020-0170-110	SH, D:1,7, R100	153,80 kg
84020-0350-130	SH, D:3,5, R300	1833,60 kg

Sorte SH, ALUMAR (Zn-Al), EN 10270-1

84022-0080-105	SH, ALUMAR, D:0,8, R50	250,00 kg
84022-0090-105	SH, ALUMAR, D:0,9, R50	306,00 kg
84022-0100-110	SH, ALUMAR, D:1, R100	611,00 kg
84022-0110-110	SH, ALUMAR, D:1,1, R100	879,00 kg
84022-0130-110	SH, ALUMAR, D:1,3, R100	1183,00 kg
84022-0180-117	SH, Zn-Al, D:1,8, R170	128,50 kg
84022-0180-504	SH, Zn-Al, D:1,8, Z2400	947,00 kg
84022-0250-120	SH, ALUMAR, D:2,5, R200	1466,00 kg

Sorte SM, phosphatiert, EN 10270-1

84030-0050-840	SM, D:0,50, DIN 355 40	190,80 kg
84030-0060-230	SM, D:0,6, KSP30	122,20 kg
84030-0075-105	SM, D:0,75, R50	33,60 kg
84030-0100-105	SM, D:1, R50	411,60 kg
84030-0110-425	SM, D:1,1, MSP250	507,60 kg
84030-0120-110	SM, D:1,2, R100	209,60 kg
84030-0190-110	SM, D:1,9, R100	536,60 kg

Wst.-Nr. 1.4310, pulverbeschichtet, EN 10270-3



85010-0020-220	302NS, D:0,2, KSP20	80,00 kg
85010-0025-220	302NS, D:0,25, KSP20	101,20 kg
85010-0030-230	302NS, D:0,3, KSP30	149,00 kg
85010-0032-230	302NS, D:0,32, KSP30	59,40 kg
85010-0035-230	302NS, D:0,35, KSP30	75,00 kg
85010-0036-230	302NS, D:0,36, KSP30	91,80 kg
85010-0040-230	302NS, D:0,4, KSP30	257,00 kg
85010-0043-230	302NS, D:0,43, KSP30	145,00 kg
85010-0045-230	302NS, D:0,45, KSP30	90,00 kg
85010-0046-420	302NS, D:0,46, MSP200	576,20 kg
85010-0050-230	302NS, D:0,5, KSP30	149,80 kg
85010-0055-230	302NS, D:0,55, KSP30	142,50 kg
85010-0056-230	302NS, D:0,56, KSP30	227,50 kg
85010-0060-230	302NS, D:0,6, KSP30	399,80 kg
85010-0062-410	302NS, D:0,62, MSP100	194,40 kg
85010-0063-413	302NS, D:0,63, MSP130	131,00 kg
85010-0065-230	302NS, D:0,65, KSP30	61,00 kg
85010-0070-230	302NS, D:0,7, KSP30	358,60 kg
85010-0075-230	302NS, D:0,75, KSP30	195,00 kg
85010-0080-135	302NS, D:0,8, R35	235,50 kg
85010-0080-230	302NS, D:0,8, KSP30	61,00 kg
85010-0090-105-VSL	302NS, D:0,9, R50, von VSL	52,00 kg
85010-0090-230	302NS, D:0,9, KSP30	302,50 kg
85010-0095-105	302NS, D:0,95, R50	53,50 kg
85010-0100-105	302NS, D:1, R50	231,00 kg
85010-0110-105	302NS, D:1,1, R50	298,00 kg
85010-0110-105-VSL	302NS, D:1,1, R50, von VSL	655,50 kg
85010-0120-105	302NS, D:1,2, R50	384,00 kg
85010-0120-105-SZF-V	302NS, D:1,2, R50, SZF, von VSL	119,00 kg
85010-0125-105	302NS, D:1,25, R50	260,50 kg
85010-0130-105	302NS, D:1,3, R50	1836,50 kg
85010-0140-110	302NS, D:1,4, R100	503,00 kg
85010-0150-110	302NS, D:1,5, R100	89,50 kg
85010-0160-110	302NS, D:1,6, R100	818,00 kg
85010-0170-110	302NS, D:1,7, R100	207,00 kg
85010-0170-425	302NS, D:1,7, MSP250	491,20 kg
85010-0175-110	302NS, D:1,75, R100	208,00 kg
85010-0180-110	302NS, D:1,8, R100	919,10 kg
85010-0190-110	302NS, D:1,9, R100	521,00 kg
85010-0200-110	302NS, D:2, R100	163,00 kg
85010-0205-120	302NS, D:2,05, R200	564,50 kg
85010-0210-120	302NS, D:2,1, R200	417,50 kg
85010-0220-110	302NS, D:2,2, R100	683,00 kg
85010-0225-120	302NS, D:2,25, R200	206,50 kg
85010-0240-120	302NS, D:2,4, R200	392,50 kg
85010-0250-125	302NS, D:2,5, R250	1053,00 kg
85010-0260-125	302NS, D:2,6, R250	750,00 kg
85010-0280-125	302NS, D:2,8, R250	506,00 kg
85010-0300-125	302NS, D:3, R250	515,00 kg
85010-0320-125	302NS, D:3,2, R250	507,00 kg
85010-0350-125	302NS, D:3,5, R250	1265,00 kg
85010-0360-125	302NS, D:3,6, R250	503,00 kg
85010-0400-125	302NS, D:4, R250	757,50 kg
85010-0450-125	302NS, D:4,5, R250	257,50 kg

85010-0500-130	302NS, D:5, R300	620,00 kg
85010-0550-130	302NS, D:5,5, R300	1235,00 kg

Wst.-Nr. 1.4310, pulverbeschichtet, EN 10270-3

85010-0560-130	302NS, D:5,6, R300	326,00 kg
85010-0700-130	302NS, D:7, R300	930,50 kg
85010-0750-130	302NS, D:7,5, R300	810,50 kg
85010-0800-130	302NS, D:8, R300	313,50 kg
85010-0850-130	302NS, D:8,5, R300	1560,00 kg
85010-1000-130	302NS, D:10, R300	1230,00 kg



Wst.-Nr. 1.4310, poliert, EN 10270-3

85011-0100-413	302NS, D:1, MSP130	136,00 kg
85011-0220-110	302NS, D:2,2, R100	138,00 kg
85011-0250-110	302NS, D:2,5, R100	153,500 kg



Wst.-Nr. 1.4310, blankgezogen, EN 10270-3

85012-0025-212	302NS, D:0,25, KSP12	48,00 kg
85012-0026-303	302NS, D:0,26, KSP3	8,80 kg
85012-0030-212	302NS, D:0,3, KSP12	96,00 kg
85012-0031-230	302NS, D:0,31, KSP30	30,00 kg
85012-0045-235	302NS, D:0,45, KSP35	105,00 kg
85012-0060-235	302NS, D:0,6, KSP35	209,00 kg
85012-0070-235	302NS, D:0,7, KSP35	140,00 kg

Wst.-Nr. 1.4310, nickelbeschichtet, EN 10270-3

85013-0035-212	302NS, D:0,35, KSP12	48,00 kg
85013-0040-235	302NS, D:0,4, KSP35	33,60 kg
85013-0070-235	302NS, D:0,7, KSP35	105,00 kg
85013-0080-235	302NS, D:0,8, KSP35	199,25 kg
85013-0090-235	302NS, D:0,9, KSP35	175,00 kg
85013-0150-110	302NS, D:1,5, R100	501,00 kg

Wst.-Nr. 1.4310, nickelpoliert, EN 10270-3

85014-0036-215	302NS, D:0,36, KSP15	30,00 kg
85014-0040-235	302NS, D:0,4, KSP35	140,00 kg
85014-0045-235	302NS, D:0,45, KSP35	383,25 kg
85014-0050-235	302NS, D:0,5, KSP35	95,50 kg
85014-0060-235	302NS, D:0,6, KSP35	140,00 kg

Wst.-Nr. 1.4310 HS, pulverbeschichtet, EN 10270-3

85020-0040-230	302HS, D:0,4, KSP30	56,50 kg
85020-0060-230	302HS, D:0,6, KSP30	122,00 kg
85020-0075-230	302HS, D:0,75, KSP30	30,60 kg
85020-0085-105	302HS, D:0,85, R50	52,40 kg
85020-0095-105	302HS, D:0,95, R50	110,50 kg
85020-0100-110	302HS, D:1, R100	158,50 kg

85020-0130-110	302HS, D:1,3, R100	309,00 kg
85020-0145-110-SZF	302HS, D:1,45, R100	184,50 kg

Wst.-Nr. 1.4401, pulverbeschichtet, EN 10270-3

85030-0050-230	316, D:0,50, KSP30	29,400 kg
85030-0090-105	316, D:0,9, R50	138,500 kg
85030-0140-110	316, D:1,4, R100	102,400 kg
85030-0150-110	316, D:1,5, R100	108,900 kg



Wst.-Nr. 1.4568, pulverbeschichtet, EN 10270-3

85040-0025-212	631, D:0,25, KSP12	36,00 kg
85040-0028-212	631, D:0,28, KSP12	132,00 kg
85040-0032-212	631, D:0,32, KSP12	48,30 kg
85040-0034-212	631, D:0,34, KSP12	22,00 kg
85040-0040-235	631, D:0,4, KSP35	35,00 kg
85040-0042-230	631, D:0,42, KSP30	199,00 kg
85040-0050-235	631, D:0,5, KSP35	105,35 kg
85040-0070-105	631, D:0,7, R50	300,00 kg
85040-0070-235	631, D:0,7, KSP35	61,30 kg
85040-0075-235	631, D:0,75, KSP35	140,00 kg
85040-0095-103	631, D:0,95, R30	30,20 kg
85040-0095-105	631, D:0,95, R50	389,60 kg
85040-0130-107	631, D:1,3, R75	461,10 kg

Wst.-Nr. 1.4571, pulverbeschichtet, EN 10088-1

85050-0110-105	316Ti, D:1,1, R50	99,00 kg
85050-0160-110	316Ti, D:1,6, R100	106,00 kg
85050-0250-125	316Ti, D:2,5, R250	514,00 kg

Wst.-Nr. 1.4571, poliert, EN 10088-1

85051-0020-220	316Ti, D:0,2, KSP20	56,80 kg
85051-0022-220	316Ti, D:0,22, KSP20	162,50 kg
85051-0025-220	316Ti, D:0,25, KSP20	82,00 kg
85051-0028-220	316Ti, D:0,28, KSP20	305,80 kg
85051-0030-220	316Ti, D:0,3, KSP20	407,00 kg
85051-0032-230	316Ti, D:0,32, KSP30	105,50 kg
85051-0035-230	316Ti, D:0,35, KSP30	121,50 kg
85051-0038-230	316Ti, D:0,38, KSP30	30,20 kg
85051-0040-230	316Ti, D:0,4, KSP30	285,50 kg
85051-0043-230	316Ti, D:0,43, KSP30	140,10 kg
85051-0045-230	316Ti, D:0,45, KSP30	184,00 kg
85051-0048-230	316Ti, D:0,48, KSP30	153,00 kg
85051-0050-230	316Ti, D:0,5, KSP30	151,50 kg
85051-0053-230	316Ti, D:0,53, KSP30	61,50 kg
85051-0055-230	316Ti, D:0,55, KSP30	153,30 kg
85051-0060-230	316Ti, D:0,6, KSP30	285,60 kg
85051-0065-230	316Ti, D:0,65, KSP30	122,40 kg
85051-0070-230	316Ti, D:0,7, KSP30	124,00 kg
85051-0075-230	316Ti, D:0,75, KSP30	251,50 kg
85051-0080-105	316Ti, D:0,8, R50	265,50 kg
85051-0085-105	316Ti, D:0,85, R50	47,00 kg

85051-0090-105	316Ti, D:0,9, R50	160,50 kg
85051-0095-105	316Ti, D:0,95, R50	107,00 kg
85051-0100-105	316Ti, D:1, R50	153,50 kg

Wst.-Nr. 1.4571, poliert, EN 10088-1

85051-0110-105	316Ti, D:1,1, R50	54,50 kg
85051-0120-105	316Ti, D:1,2, R50	53,00 kg
85051-0130-110	316Ti, D:1,3, R100	100,40 kg



Wst.-Nr. 1.4301, poliert, EN 10088-1, in Stäben á 3000 m

85061-0250-630	304, D:2,5, STB3000	3,00 kg
----------------	---------------------	---------



VDSiCr, geschält, super clean, EN 10270-2

86212-0080-715	VDSiCr, D:0,8, HSP150	1669,00 kg
86212-0085-715	VDSiCr, D:0,85, HSP150	1116,00 kg
86212-0130-720	VDSiCr, D:1,3, HSP200	1240,00 kg



VDSiCr, geschält, super clean, RD 40 my geprüft, EN 10270-2

86213-0290-145	VDSiCr, D:2,9, R450	1387,00 kg
----------------	---------------------	------------

VDSiCr, EN 10270-2

86310-0950-190	VDSiCr, D:9,5, R900	5937,00 kg
86310-1000-190	VDSiCr, D:10, R900	2987,00 kg